

Solomix P



Solomix P

Technical Data

Models	P1-1000 ZK	P1-1200 ZK	P1-1200 L ZK	P2-1200 ZK	P2-1600 ZK	P2-2000 ZK	P2-2400 ZK T
Discharge	2 Side discharge doors (front)						
Capacity m ³ ./Cu. Ft	10/350	12/430	12/430	12/430	16/570	20/715	24/860
Overall length m./Inch	4.50/178"	5.08/199"	5.27/207"	6.31/248"	6.71/264"	7.51/296"	7.59/299"
Width m./Inch	2.40/94"	2.40/94"	2.65/104"	2.18/86"	2.30/91"	2.43/96"	2.45/96"
Overall Height m./Inch*	2.77/109"	2.96/115"	2.76/109"	2.50/99"	2.77/114"	3.00/118"	3.25/128"
Width outside wheels m./Inch	1.91/75"	1.91/75"	2.13/84"	1.71/67"	1.93/77"	2.15/85"	1.87/74"
Discharge height** m./Inch	0.82/32"	0.82/32"	0.82/32"	0.83/32"	0.83/32"	0.96/38"	1.02/40"
Net weight kg./Lbs	3.915/8,630	4.110/9,150	4.225/9,295	5.425/11,935	5.825/13,000	7.075/16,400	7.975/17,600
Maximum load kg./Lbs	4.000/8,800	4.500/10,000	4.500/9,900	4.500/9,900	5.000/11,000****	7.000/19,800****	10.000/22,000
PTO Drive	540	540	540	540	540	540	540
Required hydraulic capacity							
kW/HP	50/68	55/75	60/82	60/82	62/85	75/95	80/105
Number of knives front auger	--	--	--	5	6	6	8
Number of knives rear auger	7	7	8	4	5	5	7
Tire size	400/45 L 17.5 (2 x)					435/50 R	305/70 R
						19.5 (2 x)	19.5 (4 x)
Distribution width strawbedder*** m./Inch				15-18/590-709"			
Required hydraulic capacity				20 l/min., 170 bar			
Required tractor hydraulic				1 double acting valve			

* On request different heights are possible ** Without slide *** Depending on circumstances
 **** For road transportation total weight (max. load and net weight) should not exceed 26.600 Lbs



Distribution width strawbedder: 15-18 m.



Programmable weighing computer as an option.

Standard equipment...

The Solomix P is standard equipped with Mechanically driven strawbedder at front, 50'-60' spreading width, Unique one or two auger drive system, Hand jack, Adjustable and reversible drawbar with clevis, Constant velocity PTO shaft, Two manual restrictor blades, Five-eight hardened auger knives, Two wide wheels (1000/2000) or rigid tandem axle with four wide wheels (2400 T), Two large side doors, Right, left or dual discharge, One or Two Heavy Duty planetary drives, Electric operation, Wear rim.

- Low horsepower requirement
- Mechanically driven strawbedder at front
- Optimal visibility because of strawbedder at front
- Enormous spreading width (up to 18 m./50'-60')
- One machine instead of the usual two machines



feeding

mixing

loading

cutting

Solomix P



TRIO LIET MULLOS B.V.

Hinmanweg 19
 NL-7575 BE Oldenzaal
 The Netherlands
Tel. +31 541 57 21 21
Fax +31 541 57 21 25
E-mail info@triolet.com
www.triolet.com

Trioliet: Invents for you.

Trioliet: Invents for you.